

P4



Designed for the smallest of work spaces



Compact size

Small footprint design, the compact P4 series fits into tight spaces and supports a wide range of applications.



Flexible label / Ribbon capacity

300M ribbon capacity, support face in/face out label and ribbon without any setting.



Enhanced connectivity

The P4 series has built-in Ethernet, USB host, USB device, RS-232 and it can be expanded with Wi-Fi, Bluetooth.

Applications



Retail



Manufacturing



Inventory



Health Care

General Specifications

Print Specifications	P4-250	P4-350
Print Method	Direct Thermal & Thermal Transfer	
Print Resolution	203 dpi (8 dots/mm)	300 dpi (12 dots/mm)
Print Speed (Max.)	6 ips	4 ips
Print Length (Max.)	100"(2540 mm)	50"(1270 mm)
Print Width (Max.)	4.25"(108 mm)	4.16"(105.7 mm)
Onboard Memory	32 MB SDRAM, 16MB Flash ROM (USB storage up to 32GB)	
CPU Type	32 bit RISC microprocessor	
Consumables Specifications		
Sensors	Media Transmissive sensor x 1 (fixed, 6.27mm offset) / Media Reflective sensor x 1 (movable) & Head open switch / Ribbon end sensor	
Media Type	Roll-feed, die-cut, continuous, fan-fold, black mark, tags, ticket in thermal paper or plain paper	
Media	Max. width: 4.65" (118mm). Min. width: 0.88" (22.4mm). Thickness: 0.0024"~0.0075" (0.06mm~0.19mm) 5"(127mm) OD on a 1"/1.5" (25.4/38 mm) ID core; Dealer Option external media stand 8" OD on 1"/3" ID Core	
Ribbon	Ribbon width: 1.6"~4.33"(40 mm~110mm), Ribbon length: max 300m. Core size ID 1"(25.4 mm) or 0.5"(12.7mm) Wax, Wax/Resin, Resin (Ribbon wound ink-side out or ink-side in: auto-detect)	
Fonts & Symbolologies		
Fonts	Internal character sets standard support. Soft fonts are downloadable	
1D code	UPC-A, UPC-E, JAN/EAN, CODE39, CODE93, CODE128, GS1-128 (UCC/EAN128), CODABAR (NW-7), ITF, Industrial 2 of 5, MSI, UPC add-on code, POSTNET, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Limited, GS1 DataBar Expanded, GS1 DataBar Expanded Stacked	
2D code	QR Code, PDF417 (including MicroPDF), DataMatrix (ECC200), GS1 DataMatrix, MaxiCode	
Composite Symbol	EAN-13 Composite (CC-A/CC-B), EAN-8 Composite (CC-A/CC-B), UPC-A Composite (CC-A/CC-B), UPC-E Composite (CC-A/CC-B), GS1 DataBar Composite (CC-A/CC-B), GS1 DataBar Truncated Composite (CC-A/CC-B), GS1 DataBar Stacked Composite (CC-A/CC-B), GS1 DataBar Expanded Stacked Composite (CC-A/CC-B), GS1 DataBar Expanded Composite (CC-A/CC-B), GS1 DataBar Stacked Omnidirectional Composite (CC-A/CC-B), GS1 DataBar Limited Composite (CC-A/CC-B), GS1-128 Composite (CC-A/CC-B/CC-C)	
Interface Characteristics and Integration		
Operation Interface	Standard: Button x 1, Dual LED indicators (with 3 LED colors) Factory Option: RTC	
Communication Interface	Standard: Ethernet, USB host, USB device, RS-232 Dealer Option: Wi-Fi (IEEE 802.11 b/g/n), Bluetooth	
Programming Language	PPLA+PPLB+PPLZ	
Graphics	PPLA: PCX, BMP, IMG, HEX,GDI PPLB: PCX, BMP, Binary raster, GDI PPLZ: GRF, Hex, GDI	
Software-Label Editing	Windows Driver (Windows XP/Vista/Win7/Win8/Win10), BarTender® from Seagull Scientific	
Software-Utility	Printer Tool	
Optional Accessory	Full Cutter, Partial Cutter, Peeler, External media stand	
Operating & Environment Characteristics		
Power Source	Universal Switching Power supply. AC input voltage: 100~240V, 50~60Hz. DC Output: 24V, 3.75A	
Operation Environment	Operating: 41°F~104°F (5°C~40°C). Storage: -4°F~140°F (-20°C~60°C) Operating: 25 %RH ~ 85 %RH (non-condensing). Storage: 10 %RH ~ 90 %RH(non-condensing)	
Agency Listing	CE, FCC, UL/cULus	
Physical Characteristics		
Dimensions	W 220.6 mm x H 187.5 mm x D 278.5 mm	
Weight	5.28 lbs (2.4 kg)	

*This data sheet is for informational purpose only. Argox makes no warranties, expressed or implied in this summary. Specifications are subject to change without notice. All trade marks are the property of their respective owners. For more specific information, please refer to owner's manual.



Argox Information Co., Ltd.

7F., No.126, Ln.235, Baoqiao Rd., Xindian Dist., New Taipei City 231, Taiwan (R.O.C.)

Tel: +886-2-8912-1121 Fax: +886-2-8912-1124 <http://www.argoxt.com> <https://www.youtube.com/user/argoxmkt> email:service@argox.com

Copyright © 2017, Argox Information Co., Ltd. All Rights Reserved.