

X-3120 Omnidirectional

Omni-Directional Scanner

Increase Productivity with Speedy Check Out

The X-3120 presentation scanner is a high speed which delivered a omnidirectional scan with 20 lines scan pattern which make up of 1500scans/sec.

The X-3120 is built with box casing, design with speedy barcode capturing and versatility, is suitable to use at mini market POS retail system. It is a high quality scanner with cost saving

Commonly used Applications

- Point-Of-Sales at retail stores, pharmacy and drug stores, book stores and mini markets.



Features Highlights

Decoding Speed : 1500 Scan per second

Easy operation and customise settings

Supporting the RS232, PS2 and USB interface by changing interface cable

Design for hash handling

X-3120 Omnidirectional Scanner Specification

Functional Parameters	
Light Source	650nm laser (Safe Visible Diode)
Scanning Method	20 lines Laser
Scan Resolution	0.127mm (5 mil) @ code 39, PCS=90%
Scan Pattern	Omnidirectional
Barcode types	EAN-8, EAN-13, UPC-A, UPC-E, Code 39, Code 93 , Code 128, EAN128, Codaber, Industoal 2 of 5, Interleave 2 of 5, Matrix 2 of 5, MSI, Chinese postcode etc.
Supported interfaces	RS232, PS2 keyboard, or USB
Scanning method	Automatic
Transmission rate	RS232 Baudrate:2400-38400
Decode Indicator	Buzzer and LED
Depth of field	0-220mm (pcs0.9 density 0.33mm)
Reading speed	1500 times/second
Scan Angle	5 Directions
Print Contrast	>30%(UPC EAN 100%)
Operating temperature	-200°C to 50°C
Storage temperature	-40°C to 70°C
Power voltage	5V
Operating current	270mA
Standby Power	1.0 Watts
Drop Test	Design to withstand 1.0 meter drop
Laser Class Safety	Grade 1 National Criteria for Laser Safety
Relative Humidity	5% to 95% RH(Non-condensing/non freezing)
Physical Parameter	
Exterior dimension	Length*Width*Height: 150mm*76mm*155mm
Materials	ABS + PC
Weight	665g
Cable Length	2 Meters

- ◆ Specifications and features are subjected to change without notice

Distributed By: