

RP421A THERMAL BARCODE PRINTER

- Compact and light design, easy to carry.
- Support multiple express-bill printing.
- High speed printing 150mm/s
- Integrated structure design, simple but elegant.



PRODUCTS		RP421A THERMAL BARCODE PRINTER
Printing Capability	Printing Method	Direct Thermal
	Printing Width	38-108mm
	Resolution	203dpi
	Printing Speed	127mm/s
	Paper Width	40-120mm
	Label Length	20mm~300mm
	Media Gap	Max.100mm
	Interface	USB, Bluetooth+USB
		220mm*105mm*90mm
General specifications	Dimension (LxWxH)	
	Weight RAM	1.2KG
	00000000	RAM: 2MB; FLASH: 2MB 24V/2.5A
	Power Supply Tear Cutter	Support
	Buzzer	
	, , , , , , , , , , , , , , , , , , , ,	Support
	Certificate	3C
Software	Compatibility	XP,Win03,Win7,Win8,Win10,Linux,Mac
	Printing Language	Support Multilanguage, Individual Language need to be customized
	Performance	1. Automatic paper absorption 2. Automatic paper recognition. 3. Paper out re-printing 4. Defect detecting
Environment	Working Temperature/Humidity	Temperature: 0℃—50℃ Humidity: 20%—85%
	Storage TemperatureHumidity	Temperature: -20℃-70℃ Humidity: 5%-95%