

# CTM- 1700 17" CAPACITIVE TOUCH SCREEN MONITOR



## **FUNCTIONS:**

- 17" TFT LCD HIGH CONTRAST panel TV/AV/HDMI optional
- High-precision Four/Five wires resistive touch function.
- (USB port/COM RS232 optional)
- 10-points capacitive touch panel (5-Wire Touch panel Optional)
- Standard VGA (15 pin D-SUB RGT) Video input RS232/COM/USB touch panel connectors
- High native resolution & High contrast and brightness & Wide viewing angle
- Sensitive touch-screen, quick response
- Operating All Systems: DOS/Windows 9X ME 2K XP, Win 7, Vista, Win 10
- Low radiation and consumption. High reliability Good stability HDMI MODE support,480I/480P/720P(50)/720P(60)/576I/576P/1080I(50)/1080P(50)/1080I(60)/1080P(60)
- With VESA hole, Easy to install and maintain

## Product Specification

Backlight	TFT LED Backlight	
LCD Panel	15" A GRADE Panel	
Display Type	4:3 Ratio	
Pixel Pitch	0.107 (W) X 0.372(H) mm	
Brightness	350 cd/m2	
Native Resolution	1280*1024 optional	
Contrast Ratio Typically	1000:01:00	
Viewing Angle	170° /160°	
Input Video Format	Analog RGB ,NTSC/PAL/SCAME(AUTO)	
Colors	16.7 million	
Backlight Lamp life Hrs	50,000	
Sychronization Range(H/V)	37.9-74.6 KHZ , 60-85 HZ	
Touch function	Touch type	10 POINTS CAPACITIVE TOUCH PANEL( 4-wire 5 wire resistive optional)
	Touch screen Interface	Serial COM(RS232) or USB
	Touch Response Time	8 ms
	Touch Sensitivity	Fixed
	Touch Pen Hitting Life	>= 1milions times
OSD Languages	8 Languages	
Power Supply	AC220v – DC12V	
Power Consumption	<25 W Typ	
Temperature Range:	Operating:0℃-60℃, Storage:-20℃ -80℃	
Humidity Non Condensing	Operating:10%-90%, Storage	
Color	Black	
Weight	4.35 kg	
Warranty	1 year warranty and 3 years free	
gency Approvals	FCC, CE, ROHS	